

Polycom® QDX 6000™

High-Resolution Video Conferencing System

The perfect balance of quality, performance, simplicity and affordability

Rapid ROI and Increased Productivity

For organisations looking to greatly enhance productivity and communication quality, the Polycom QDX® 6000™ high-resolution video conferencing system combines unprecedented performance at low bandwidths with simplified set-up and ease of use.

The Polycom QDX 6000 accelerates organisational ROI by reducing travel between geographically dispersed sites, improves communication between teams and individuals, and enables faster and more informed knowledge sharing.

By making video deployable across a wider array of environments, the QDX 6000 enables organisations to implement video conferencing without dedicated IT resources and with minimal network impact. Delivering lifelike meeting experiences and powerful content sharing capabilities, the QDX 6000 provides an optimal price-to-performance ratio for non-HD video applications.

High-Resolution Video Conferencing, Simple to Install and Use

Leveraging a powerful codec, studio-quality camera, CD-quality audio, and multiple video inputs and outputs, the QDX 6000 is compatible with all standards-based video conferencing systems, conference bridges, firewall traversal products, and more. With highly secure AES encryption of video and audio communications and intuitive interfaces, users can securely call others and enter a video conference in seconds. Content and other media is shared via a simple point-and-click interface, while Polycom Lost Packet Recovery™ technology provides smooth and uninterrupted conference experiences, even on congested networks.

Simple to install and easy to use, the Polycom QDX 6000 is an ideal solution for benefitting from the cost-savings and productivity enhancements of video conferencing.



Benefits

- Simplified installation and ease of use
- Natural lifelike communication at low bandwidths
- Smooth and uninterrupted video conferences, even across congested networks
- Superb audio clarity to hear every word, conversation, and speaker
- Improved meeting quality with simultaneous speaker and content views
- Improved collaboration with intuitive one-touch content sharing

Polycom QDX 6000 Specifications

Model Available

Polycom QDX 6000 package includes:
Polycom EagleEye III Camera, codec, two microphones, cables and remote control

Video Standards & Protocols

- H.264, H.263, H.261

People Video Resolution

- 4SIF/4CIF 16:9 at 256 Kbps—4 Mbps
- SIF (352 x 240), CIF (352 x 288)
- QSIF (176 x 120), QCIF (176 x 144)

Video Input

- 2 x S-Video, one with DB9 for Polycom EagleEye camera
- 2 x Composite
- 1 x VGA

Video Output

Main monitor

- Component 720p
 - 1 x S-Video
 - 1 x RCA

Second monitor

- VGA, or:
 - 1 x S-Video
 - 1 x RCA

Camera

- Polycom EagleEye III Camera
 - SMPTE 296M 1280 x 720p60 SMPTE 274M 1920 x 1080p, 60/50
 - 12x optical zoom
 - 72° FOV min

Audio Standards & Protocols

- Polycom StereoSurround™
- 22 kHz bandwidth with Polycom Siren™ 22
- 20 kHz bandwidth with G.719
- 14 kHz bandwidth with Polycom Siren 14, G.722.1 Annex C
- 7 kHz bandwidth with G.722, G.722.1
- 3.4 kHz bandwidth with G.711, G.728
- Automatic gain control
- Automatic noise suppression
- Instant adaptation echo cancellation
- Audio error concealment

About Polycom

Polycom is the global leader in standards-based unified communications (UC) solutions for telepresence, video, and voice powered by the Polycom® RealPresence™ Platform. The RealPresence Platform interoperates with the broadest range of business, mobile, and social applications and devices. More than 400,000 organizations trust Polycom solutions to collaborate and meet face-to-face from any location for more productive and effective engagement with colleagues, partners, customers, and prospects. Polycom, together with its broad partner ecosystem, provides customers with the best TCO, scalability, and security—on-premises, hosted, or cloud delivered.

For more information, visit www.polycom.com, call 1-800-POLYCOM, or contact your Polycom sales representative.

Polycom Worldwide Headquarters
4750 Willow Road, Pleasanton, CA 94588
1.800.POLYCOM or +1.925.924.6000
www.polycom.com



Audio Input

- 2 x RJ9 for Polycom analog microphones
- 2 x Dual RCA

Audio Output

- 2 x Dual RCA

Other ITU-Supported Standards

- H.224 far-end camera control
- H.323 Annex Q far-end camera control
- H.225, H.245, H.241
- H.239 dual stream
- H.460 NAT/firewall traversal

Network

- Interfaces
 - 10/100 auto NIC switch, RJ45 connector
 - H.323 / SIP up to 4 Mbps
 - Lost Packet Recovery™ (LPR™) for QoS
- 2 x RS232 (1 x camera control)
 - Data pass through
 - Full serial API support

User Interface

- Directory services
- System management
 - Web-based
 - SNMP
- CDR
- International languages (16)
- Message overlay
- Customizable logo
- Polycom Converged Management Application™ (CMA™)
- Security

Security mode

- Embedded AES FIPS 197, H.235V3 and H.233/234

Content

- Content sharing (H.239)
 - Polycom People+Content™ IP

Electrical

- Auto sensing power supply

- Typical operating voltage/power 127VA @ 115V @ 60 Hz @ .57 PF
- Typical operating voltage/power 163VA @ 230V @ 60 Hz @ .44 PF
- Typical operating voltage/power 152VA @ 230V @ 50 Hz @ .47 PF

These numbers were empirically collected under TYPICAL operating conditions. No attempt was made to force max power consumption

Environmental Specification

- Operating temperature: 0—40°C
- Operating humidity: 10—80%
- Non-operating temperature: -40°—70° C
- Non-operating humidity (non-condensing): 10—90%
- Maximum altitude: 10,000 feet

Physical Characteristics

- Polycom QDX 6000 series base box (1U): 1.7" x 17.2" x 10.2" (H/W/D)

Warranty

- One-year return to factory parts and labor

Technical Documentation

- Award-winning documentation for setting up, maintaining, and using the system available at www.polycom.com/videodocumentation

Options

- Polycom Media Cart
 - 2583-26914-001
- EagleEye QDX flat panel/wall mounting shelf
 - 2215-24143-001
- Stereo Speaker Kit
 - 2200-21969-120 (120V)
 - 2200-21969-240 (240V)
- EagleEye Camera Cable
 - 2457-30821-002 (10 m)
- Wireless Microphone Kit
 - 2200-32400-001